

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	J9379B-REF

HPE MSM310 Access Point WW - Radio access point - 100Mb LAN - Wi-Fi

The HP E-series MSM Access Points are managed by any of the HP E-series MSM controllers and the HP RF manager for the RF security sensors. The HP E-series Access Points can also work in autonomous mode. The HP E-series MSM Access Points are IEEE802.3af compliant.

Specifikation

General

Status	R4
Device Type	Radio access point
Width	16.3 cm
Depth	16.9 cm
Height	4.8 cm
Weight	1.4 kg

Networking

Form Factor	External
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g
Communication Mode	Half-duplex, full-duplex
Features	Wi-Fi Multimedia (WMM) support
Encryption Algorithm	TLS, PEAP, TTLS, WPA-Enterprise, WPA2-Enterprise
Authentication Method	MS-CHAP v.2
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11a, IEEE 802.3af, IEEE 802.11d, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11h

Aerial

Antenna	External detachable
----------------	---------------------

Antenna Qty	2
Directivity	Omni-directional
Gain Level	2 dBi

Expansion / Connectivity

Interfaces	2 x 100Base-TX - RJ-45 1 x management - DB-9 2 x aerial
-------------------	---

Miscellaneous

Compliant Standards	EN55022 Class B, ICES-003 Class B, FCC Part 15 B, FCC Part 15.247, OET 65 C, RSS-210, RSS-102, MIC, UL 2043, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-03, EN 300.489.1, FCC Part 15.407, ARIB STD-T66, ARIB STD-T71, RCR STD-33, EN 300 328, EN 301 893, EN 301 489-17
----------------------------	--

Power

Power Over Ethernet (PoE) Supported	PoE
Power Consumption Operational	6.5 Watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	45 °C
Humidity Range Operating	0 - 95%