

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	JL087AR

HPE Aruba X372 - Power supply - hot-plug / redundant - AC 110-240 V - 1050 Watt - for HPE Aruba 2930M 24, 2930M 24G, 2930M 40G, 2930M 48G, 3810M 24G, 3810M 40G, 3810M 48G

Specifikation

General

Status	W2
Device Type	Power supply - hot-plug / redundant
Device Type	Power supply - hot-plug / redundant

Power Device

Input Voltage	AC 110-240 V
Input Voltage	AC 110-240 V
Output Voltage	54 V
Output Voltage	54 V
Power Capacity	1050 Watt
Power Capacity	1050 Watt

Dimensions & Weight

Width	8.31 cm
--------------	---------

Miscellaneous

Pricing Type	Remarketed
---------------------	------------

Dimensions & Weight

Depth	22.56 cm
Width	8.31 cm
Depth	22.56 cm
Height	4.01 cm

Height	4.01 cm
Weight	880 g
Weight	880 g

Compatibility Information

Designed For	HPE Aruba 2930M 24 Smart Rate POE+ 1-Slot, 2930M 24G POE+ 1-Slot, 2930M 40G 8 HPE Smart Rate PoE+ 1-slot Switch, 2930M 48G POE+ 1-Slot, 3810M 24G PoE+ 1-slot Switch, 3810M 40G 8 HPE Smart Rate PoE+ 1-slot Switch, 3810M 48G PoE+ 1-slot Switch, 3810M 48G PoE+ 4SFP+ 1050W, 3810M 48G PoE+ 4SFP+ 680W
Designed For	HPE Aruba 2930M 24 Smart Rate POE+ 1-Slot, 2930M 24G POE+ 1-Slot, 2930M 40G 8 HPE Smart Rate PoE+ 1-slot Switch, 2930M 48G POE+ 1-Slot, 3810M 24G PoE+ 1-slot Switch, 3810M 40G 8 HPE Smart Rate PoE+ 1-slot Switch, 3810M 48G PoE+ 1-slot Switch, 3810M 48G PoE+ 4SFP+ 1050W, 3810M 48G PoE+ 4SFP+ 680W