

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	P01880-B21R

HPE ProLiant DL360 Gen10 Low - rack-mountable - Xeon Bronze 3104 1.7 GHz - 8 GB - no HDD

Does your data center need a secure, performance driven dense server that you can confidently deploy for virtualization, database, or high-performance computing? The powerful ProLiant DL360 Gen10 is redefining dense compute by delivering security, agility and incredible expandability businesses want. Deploy this dense platform for diverse workloads in space constrained environments and maintain it with ease by automating essential server lifecycle management tasks.

Specifikation

General

Status	W2
Type	Server
Product Form Factor	Rack-mountable - 1U
Built-in Devices	Led panel
Server Scalability	2-way
Hot-Swap Bays Qty	4

Processor / Chipset

CPU	Intel Xeon Bronze 3104 / 1.7 GHz
Number of Cores	6-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621

Cache Memory

Installed Size	L3 Cache - 8.25 MB
-----------------------	--------------------

Cache Per Processor	8.25 MB
RAM	
Installed Size	8 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2133 MHz
Rated Memory Speed	2666 MHz
Memory Specification Compliance	PC4-21333
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, dual rank, slots 13 - 24 are available in two-processor configuration only
Configuration Features	1 x 8 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x SATA
Controller Interface Type	SATA 6Gb/s
Storage Controller Name	HPE Smart Array S100i SR Software
Channel Qty	14
Optical Storage	
Type	No optical drive
Card Reader	
Type	Card reader
Supported Flash Memory Cards	microSD
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	4 x Gigabit Ethernet
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support

Expansion / Connectivity	
Bays	1 (total) / 1 (free) x external 4 (total) / 4 (free) x hot-swap 3.5" LFF
Slots	1 (total) / 1 (free) x FlexibleLOM - three-quarter-length, full-height (low-profile) 1 (total) / 1 (free) x PCIe 3.0 x16 - full-height 1 (total) / 1 (free) x PCIe 3.0 x8 (low-profile) 1 (total) / 1 (free) x microSD Card (internal)
Interfaces	1 x HP iLO - Type A (1 in front) 5 x USB 3.0 (1 front, 2 rear, 2 internal) 4 x LAN (Gigabit Ethernet) - RJ-45 (4 rear) 1 x HP iLO - RJ-45 (1 rear) 1 x VGA (1 rear)
Miscellaneous	
Included Accessories	CPU standard heatsink, 5 x standard hot plug fans
Cables Included	Power cable
Compliant Standards	AES, FIPS 140-2, IPv6 Ready, PCI DSS, TLS v1.2, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	500 Watt
Operating System / Software	
OS Certified	CentOS, Microsoft Windows Server 2012 R2, VMware vSphere 6.0 (ESXi), SuSE Linux Enterprise Server 11 SP4, Microsoft Windows Server 2016, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 6.9, VMware vSphere 6.5 (ESXi), SuSE Linux Enterprise Server 12 SP2, ClearOS
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site - response time: next business day
Dimensions & Weight	
Width	43.46 cm
Depth	70.7 cm
Height	4.29 cm
Weight	13.04 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)

Sound Emission

38.1 dBA

