

## Produktinformation



### Information

|                    |                            |
|--------------------|----------------------------|
| <i>Tillverkare</i> | Hewlett Packard Enterprise |
| <i>Artnr</i>       | QK769A-REF                 |

## HPE StorageWorks Disk Enclosure D2700 - Storage enclosure - 25 bays (SATA-300 / SAS-2) - HDD 1 TB x 25 - rack-mountable - 2U

Manage your small and midrange business growing storage needs by deploying the next generation 6 Gb SAS low cost, flexible tiered external storage system. It is ideal for small application environments in SMBs, remote offices and departmental locations as well as tier 2 or 3 storage for enterprise customers. The 6 Gb SAS enclosures - Small Form Factor (SFF) D2700 with 25 drive bays - offers modular solutions to simplify capacity expansion of HP ProLiant server environments to external storage without having to make the full move to SAN or NAS. The HP StorageWorks D2000 series Disk Enclosures is a family of disk drive storage enclosure with 6 Gb SAS host connectivity. The D2000 series is a 2U direct attach, external shared storage solution designed for small to medium size deployments or remote locations. These enclosures deliver industry-leading availability, storage density, and upgradeability to meet customers' demanding and growing storage needs. The D2000 series delivers the ideal mix of low-cost and high capacity, for minimum I/O workloads such as reference data, archival, and disk-to-disk backup.

## Specifikation

### General

|                       |                     |
|-----------------------|---------------------|
| <b>Status</b>         | R4                  |
| <b>Device Type</b>    | Storage enclosure   |
| <b>Enclosure Type</b> | Rack-mountable - 2U |

### Chassis

|  |                  |
|--|------------------|
| <b>Installed Devices / Modules Qty</b> | 25               |
| <b>Supported Devices / Modules Qty</b> | 25               |
| <b>Supported Drives</b>                | SATA-300 / SAS-2 |

### Storage

|                               |       |
|-------------------------------|-------|
| <b>Max Supported Capacity</b> | 15 TB |
|-------------------------------|-------|

### Processor

|             |        |
|-------------|--------|
| <b>Type</b> | No CPU |
|-------------|--------|

### Hard Drive

|             |                |
|-------------|----------------|
| <b>Type</b> | HDD - hot-swap |
|-------------|----------------|

|                       |           |
|-----------------------|-----------|
| <b>Capacity</b>       | 25 x 1 TB |
| <b>Interface Type</b> | SAS 6Gb/s |
| <b>Spindle Speed</b>  | 7200 rpm  |

Expansion / Connectivity

|                       |   |
|-----------------------|---|
| <b>Expansion Bays</b> | 25 (total) / 0 (free) x hot-swap - 2.5" SFF |
| <b>Interfaces</b>     | 1 x SAS 6Gb/s                               |

Miscellaneous

|                          |                       |
|--------------------------|-----------------------|
| <b>Cables Included</b>   | 1 x SAS cable - 50 cm |
| <b>Rack Mounting Kit</b> | Included              |

Power

|                                |                                      |
|--------------------------------|--------------------------------------|
| <b>Power Device</b>            | 2 x internal power supply - hot-plug |
| <b>Max Supported Qty</b>       | 2                                    |
| <b>Power Redundancy</b>        | Yes                                  |
| <b>Power Redundancy Scheme</b> | 1+1                                  |
| <b>Voltage Required</b>        | AC 120/230 V - 50/60 Hz              |
| <b>Power Provided</b>          | 300 Watt                             |

Dimensions & Weight

|               |         |
|---------------|---------|
| <b>Width</b>  | 45 cm   |
| <b>Depth</b>  | 56.7 cm |
| <b>Height</b> | 8.8 cm  |
| <b>Weight</b> | 17.2 kg |

Environmental Parameters

|                                  |          |
|----------------------------------|----------|
| <b>Min Operating Temperature</b> | 10 °C    |
| <b>Max Operating Temperature</b> | 35 °C    |
| <b>Humidity Range Operating</b>  | 10 - 90% |