

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	R0Q78A

HPE Modular Smart Array 2060 12Gb SAS SFF Storage - Hard drive array - 0 TB - 24 bays (SAS-3) - SAS 12Gb/s (external) - rack-mountable - 2U

The HPE MSA 2060 storage is a flash-ready hybrid storage system designed to deliver hands-free, affordable application acceleration for small and remote office deployments. It gives you the combination of simplicity, flexibility, and advanced features. With the ability to deliver 325.000 IOPS, the HPE MSA 2060 is faster with ample horsepower for even more demanding workloads.

Specifikation

General

Device Type	Hard drive array
Enclosure Type	Rack-mountable - 2U

Chassis

Installed Devices / Modules Qty	0
Supported Devices / Modules Qty	24
Supported Drives	SAS-3

Storage

Total Array Capacity	0 TB
Max Supported Capacity	921.6 TB
HDD Array External Interface	SAS 12Gb/s
Maximum LUNs	512

Processor

CPU	No CPU
------------	--------

Storage Controller

Type	RAID
Installed Qty	2

Interface Type	SAS 12Gb/s
Data Transfer Rate	1.2 GBps
Cache / Buffer Size (Max)	24 GB
Max Storage Devices Qty	240
RAID Level	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 50

Storage Controller (2nd)

Installed Qty	2
----------------------	---

Hard Drive

Type	No HDD
-------------	--------

Expansion / Connectivity

Expansion Bays	24 (total) / 24 (free) - 2.5" SFF
Interfaces	8 x SAS 12Gb/s 2 x mini-USB 2.0 (management) 2 x Ethernet 1000Base-T (management) - RJ-45

System Requirements

OS Required	HP-UX, SuSe Linux, Apple MacOS X, Microsoft Windows, Red Hat Enterprise Linux, HP OpenVMS, Microsoft Windows Server 2012, VMware ESXi 5.x, Microsoft Windows Server 2012 R2, Microsoft Windows Server 2012 R2 with Hyper-V, VMware ESXi 6.x
--------------------	---

Miscellaneous

Features	SNMP support, SMTP support
Included Accessories	Rack mounting kit

Environmental Standards

ENERGY STAR Certified	Yes
------------------------------	-----

Power

Power Device	2 x internal power supply - hot-plug
Max Supported Qty	2
Power Redundancy	Yes
Power Redundancy Scheme	1+1
Voltage Required	DC -48 V
Power Provided	764 Watt

Manufacturer Warranty

Service & Support	Limited warranty - parts - 3 years
------------------------------	------------------------------------