

Produktinformation



Information

lenovo

Tillverkare Lenovo
Artnr 10KGS0L600

Lenovo ThinkCentre M600 - tiny - Celeron N3010 1.04 GHz - 2 GB - SSD 16 GB

ThinkCentre M600 Tiny is an ultrasmall form factor. It offers mounting solutions, including support for standard VESA mounts and Tiny-in-One configurations - which transform your PC into a space-saving modular all-in-one. Tiny desktops fit just about anywhere, while still delivering reliable, enterprise-level performance. Maximize productivity with independent display support for up to three monitors. The expanded work area and easier navigation between applications help reduce errors and improve productivity as you extend your desktop across multiple monitors. If you choose to mount this compact unit on the back of your monitor, you can still power on conveniently from the front, by simply pressing Alt+P on a USB-connected keyboard. Also compatible with wireless keyboards. Move data between the M600 Tiny and other devices quickly with USB 3.0 - it's faster and backward-compatible.

Specifikation

General

Status	N1
Type	Thin client
Product Form Factor	Tiny
Built-in Devices	Speaker
Embedded Security	Trusted Platform Module (TPM 1.2) Security Chip
Colour	Black

Processor / Chipset

CPU	Intel Celeron N3010 / 1.04 GHz
Max Turbo Speed	2.24 GHz
Number of Cores	Dual-Core
CPU Qty	1
Max CPU Qty	1
Processor Main Features	Intel Burst Technology

Cache Memory

Installed Size	2 MB
-----------------------	------

Cache Per Processor	2 MB
RAM	
Installed Size	2 GB / 8 GB (max)
Technology	DDR3L SDRAM - non-ECC
Effective Memory Speed	1600 MHz
Rated Memory Speed	1600 MHz
Form Factor	SO-DIMM 204-pin
Slots	1 (Total) / 0 (empty)
Features	Low-voltage
Configuration Features	1 x 2 GB
Hard Drive	
Type	SSD - M.2 2242
Capacity	1 x 16 GB
Interface Type	SATA 6Gb/s
Storage Controller	
Type	1 x SATA
Controller Interface Type	SATA 6Gb/s
Channel Qty	1
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Graphics Processor	Intel HD Graphics 400
Video Interfaces	DisplayPort
Max Monitors Supported	2
Audio Output	
Sound Output Mode	Stereo
Compliant Standards	High Definition Audio
Networking	
Ethernet Controller	Realtek RTL8111GN
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL)
Expansion / Connectivity	
Bays	1 (total) / 1 (free) x internal 2.5"
Slots	1 (total) / 0 (free) x SO-DIMM 204-pin 1 (total) / 0 (free) x CPU

Interfaces	4 x USB 3.0 (2 front, 2 rear) (one of them is Always On and fast-charging) 1 x microphone (1 in front) 1 x headphones/microphone (1 in front) 2 x USB 2.0 1 x LAN (Gigabit Ethernet) 2 x DisplayPort 1 x headphones
Miscellaneous	
Theft/Intrusion Protection	Security lock slot (cable lock sold separately), padlock loop, chassis intrusion switch
Security Slot Type	Kensington security slot
Compliant Standards	RoHS, GREENGUARD, Energy-Related Products (ErP) Lot 3
Power	
Device Type	Power adapter
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	65 Watt
Efficiency	88%
Dimensions & Weight	
Width	17.9 cm
Depth	18.29 cm
Height	3.45 cm
Weight	1.3 kg