

Produktinformation



Information

lenovo

Tillverkare Lenovo
Artnr 61C1RAT2EU

Lenovo ThinkVision P32u-10 - LED monitor - 4K - 32"

The Lenovo ThinkVision P32u-10 display makes your creative ideas come to life. It delivers lightning-fast, one-cable connection for power, data, video and audio. At the same time, you can truly boost productivity and enjoy a stunning visual experience by connecting dual monitors via Thunderbolt 3 out.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	32"
Viewable Size	32"
Built-in Devices	USB 3.0 hub
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.1845 mm
Vertical Refresh Rate	23 - 80 Hz
Horizontal Refresh Rate	30 - 160 kHz
Backlight Technology	LED backlight
Colour	Raven black
Dimensions (WxDxH)	72.67 cm x 35 cm x 49.78 cm - with stand
Weight	10 kg

Connectivity

Interfaces	2 x HDMI Thunderbolt 3 DisplayPort USB 3.0 upstream 4 x USB 3.0 downstream Audio line-out (mini-jack)
-------------------	---

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+30

Swivel Angle	90
Rotation Angle	180
Height Adjustment	110 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately)
Compliant Standards	DDC/CI, VESA TMDS
Localisation	English / Europe
Security Slot Type	Kensington security slot

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	57 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption Sleep	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt

Software / System Requirements

OS Required	Microsoft Windows 7 / 10 (32/64 bits)
--------------------	---------------------------------------

Dimensions & Weight

Dimensions & Weight Details	Without stand - width: 72.67 cm - depth: 6.33 cm - height: 43.15 cm - weight: 6.9 kg With stand - width: 72.67 cm - depth: 35 cm - height: 49.78 cm - weight: 10 kg
--	---

Environmental Standards

TCO Certified	TCO Certified Displays 7, TCO Certified Edge Displays
ENERGY STAR Certified	Yes

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 80% (non-condensing)