

Produktinformation



Information

NETGEAR

Tillverkare NETGEAR
Artnr RN21400-100NES

NETGEAR ReadyNAS 214 - NAS server - 4 bays - SATA 3Gb/s - RAID 0, 1, 5, 6, 10, JBOD - RAM 2 GB - Gigabit Ethernet - iSCSI

The ReadyNAS 210 is powered by a quad core Cortex A15 1.4GHz processor, has 2 Gigabytes of RAM, dual Gigabit Ethernet ports with Link Aggregation technology and delivers up to 200MByte/sec data transfer speed. It offers the industry's leading feature of 5 levels of protection on your documents, photos, videos and all types of data. The ReadyCLOUD portal-based user interface and app on PC, Mac, smartphones and tablets make the RN210 the ideal choice for consumers because of its simplicity and ease of use.

Specifikation

General

Device Type	NAS server
Host Connectivity	Gigabit Ethernet
Max Supported Capacity	24 TB
Installed Devices / Modules Qty	4 (max)
Width	22 cm
Depth	10.1 cm
Height	14.2 cm
Weight	2.03 kg

Processor / Memory

Processors Installed	1 x Cortex-A15 1.4 GHz
Number of Cores	Quad-Core
RAM	2 GB
Flash Memory Installed	128 MB

Storage Controller

Type	1 x RAID
Interface Type	SATA 3Gb/s

RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, JBOD
Networking	
Data Link Protocol	10Mb LAN, 100Mb LAN, GigE
Network / Transport Protocol	TCP/IP, NTP, FTP, DHCP, Bonjour, SMB
Remote Management Protocol	SNMP 2, SNMP 3, SSH
Network Services Compatibility	Microsoft Active Directory (AD), DHCP, Microsoft CIFS, Network File System (NFS), FTP, Server Message Block (SMB), Apple File Protocol (AFP), HTTP, HTTPS
Features	Wake on LAN (WOL), E-mail alert, IPv6 support, Access Control List (ACL) support, SSH support, Jumbo Frames support, static IP mode, IPv4 support, dynamic IP mode, DHCP client, WebDAV server, Dropbox support, anti-virus protection
Encryption Algorithm	256-bit AES
Compliant Standards	IEEE 802.3ad (LACP), UPnP
Expansion / Connectivity	
Expansion Bays	4 (total) / 4 (free) x hot-swap - 2.5" / 3.5"
Interfaces	2 x Ethernet 1000Base-T - RJ-45 3 x USB 3.0 1 x eSATA
Miscellaneous	
Features	Security lock slot (cable lock sold separately), X-RAID2 technology, LED indicator, built-in cooling fan, UPS support, auto shutdown circuit, VPN support, one-touch copy button
Compliant Standards	FCC Class B certified, RoHS, AES-256, VCCI Class B
Power	
Power Device	External power adapter
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	60 Watt
Software / System Requirements	
Storage Operating System	ReadyNAS OS 6.2
OS Required	UNIX, Apple MacOS, Linux, Microsoft Windows Server 2008 R2, Android, Microsoft Windows 7 (32/64 bits), Apple iOS, Microsoft Windows Server 2012, Windows 8 (32/64 bits), Windows 8.1 (32/64 bits)
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 95% (non-condensing)