

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	AP9619-REF

APC Network Management Card with Environmental Monitoring - Remote management adapter - 100Mb LAN - 100Base-TX - for AIS; Silcon; Smart-UPS XL 1000, XL Network Package for Server Rooms; Symmetra RM

APC's UPS Network Management Cards provide management of your UPSs by connecting the UPS directly to the network with a dedicated IP address, avoiding the need for a proxy such as a server. Embedded technology provides exceptional reliability and enables the UPS to reboot hung equipment. Manage each APC UPS individually via web browser, Telnet or SSH. Notification features inform you of problems as they occur. For protected servers, graceful unattended shutdown is provided in case of extended power outages. The AP9619 Management Card includes an Integrated Environmental Monitor that provides the following features: A temperature sensor; Two input contacts; Two-position output relay. In addition to the Integrated Environmental Monitor, an AP9619 Management Card can also monitor and manage an Environmental Monitoring Card. The Management Card can be installed into the following APC devices: any Smart-UPS or Matrix-UPS model that has an internal expansion slot, as well as any Silcon, Symmetra, or Symmetra PX UPS. A Silcon UPS, which does not have an expansion slot, requires using a Silcon Triple Expansion Chassis (AP9604S).

Specifikation

General

Status	R4
Device Type	Remote management adapter
Form Factor	Plug-in module

Networking

Connectivity Technology	Wired
Cabling Type	Ethernet 10Base-T, Ethernet 100Base-TX
Data Link Protocol	Ethernet, Fast Ethernet
Data Transfer Rate	100 Mbps
Network / Transport Protocol	TCP/IP

Remote Management Protocol	SNMP, Telnet, HTTP
Features	DHCP support, BOOTP support, E-mail alert, event log
Expansion / Connectivity	
Interfaces	1 x 100Base-TX - RJ-45 1
Compatible Slots	1 x Expansion Slot
Miscellaneous	
Included Accessories	Temperature and humidity sensor
Encryption Algorithm	SSL
Compliant Standards	FCC Class A certified, VCCI, C-Tick, BSMI, EN55024, EN55022 Class A
Software / System Requirements	
Software Included	Drivers & Utilities
Dimensions & Weight	
Width	12.1 cm
Depth	10.8 cm
Height	3.8 cm
Weight	140 g
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Max Altitude Operating	3 km
Compatibility Information	
Designed For	IBM Smart-UPS XL APC AIS APC Matrix-UPS APC Silcon APC Smart-UPS 1000, 1000VA USB & Serial, 1400, 1400VA XL, 1500, 1500VA USB, 1500VA USB & Serial, 2200, 2200VA XL, 3000, 3000NET, 3000RM, 3000RM3U, 3000VA, 3000VA USB & Serial, 3000VA USB & Serial w/ AP9617 and SU027RM2U, 3000VA XL, 5000VA, 5000VA XL, 500VA, 500VA USB & Serial, 700, 700RM, 700VA, 700VA XL, 750, 750VA USB & Serial, 750VA USB XL, 750VA XL USB & Serial, DP 10000, DP 4000, DP 6000, DP 8000, XL 1000VA, XL 750VA USB & Serial, XL Modular 1500VA, XL Modular 3000VA, XL Network Package for Server Rooms APC Smart-UPS NS APC Smart-UPS On-Line APC Smart-UPS RM APC Smart-UPS RT APC Smart-UPS VT APC Symmetra APC Symmetra LX APC Symmetra PX APC Symmetra RM