

## Produktinformation



### Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	BR650MI

## APC Back-UPS Pro BR650MI - UPS - AC 230 V - 390 Watt - 650 VA - USB - output connectors: 6 - black

The APC Back-UPS Pro models provide premium battery backup and surge protection. Ideal for home or small office electronics, networking devices, gaming PCs and consoles. APC Back-UPS Pro models provide sinewave output, USB charging ports for your mobile devices, and increased runtime for your critical electronics.

## Specifikation

### General

<b>Device Type</b>	UPS - external
<b>Colour</b>	Black

### Power Device

<b>UPS Technology</b>	Line interactive
<b>Input Voltage</b>	AC 230 V
<b>Input Voltage Range</b>	AC 176 - 294 V
<b>Frequency Provided</b>	50/60 Hz $\pm$ 1Hz
<b>Frequency Required</b>	50/60 Hz $\pm$ 3Hz
<b>Input Connectors</b>	1
<b>Power Output Connectors Details</b>	6 x power (UPS and surge)
<b>Output Voltage</b>	AC 230 V $\pm$ 8% - 50/60 Hz
<b>Power Capacity</b>	390 Watt / 650 VA
<b>Dataline Surge Protection</b>	Ethernet 10/100/1000Base-T - RJ-45 - 1 input line / 1 output line Phone line - 1 input line / 1 output line
<b>Output Waveform</b>	Stepped approximation to a sinewave
<b>Surge Energy Rating</b>	557 Joules
<b>Circuit Protection</b>	Circuit breaker
<b>Power Factor (PF)</b>	0.6

Battery	
<b>Technology</b>	Lead Acid
<b>Run Time (Up To)</b>	3 min at full load 10.5 min at half load 4 min at 335 Watts 7 min at 240 Watts 20 min at 119 Watts 64 min at 40 Watts
<b>Recharge Time</b>	12 hours
Networking	
<b>Remote Management Interface</b>	USB
Expansion / Connectivity	
<b>Interfaces</b>	Management (USB)
Miscellaneous	
<b>Cables Included</b>	Power cable 1.83 m USB cable
<b>Equipment Protection Value</b>	150000 Euros
<b>Features</b>	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), overload protection, dataline protection
<b>Compliant Standards</b>	TUV GS, EMC, IP20, KETI, EAC, RCM, TISI, CB 60950
Software / System Requirements	
<b>Software Included</b>	APC PowerChute Personal Edition
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 3 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
Dimensions & Weight	
<b>Width</b>	9.1 cm
<b>Depth</b>	31 cm
<b>Height</b>	19 cm
<b>Weight</b>	6.4 kg
Dimensions & Weight (Shipping)	
<b>Shipping Width</b>	44 cm
<b>Shipping Depth</b>	14.3 cm
<b>Shipping Height</b>	25.5 cm
<b>Shipping Weight</b>	7.4 kg