

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	BX1400UI

APC Back-UPS 1400VA - UPS - AC 230 V - 700 Watt - 1400 VA - USB - output connectors: 6 - black

APC's Back-UPS 1400 protect your electronic equipment from damage due to power outages, surges and spikes while providing short term battery power during an outage. The Back-UPS 1400 features Automatic Voltage Regulation (AVR), which instantly adjusts high and low voltage fluctuations to safe levels for your electronics, saving battery power for when you need it most during storms and power outages. Additionally, Australian sockets make for easy-to-use connection of protected equipment. Specifically designed to protect your PC equipment and network connection in harsh power environments, the Back-UPS 1400 ensures maximum productivity and work efficiency.

Specifikation

General

Device Type	UPS - external
Colour	Black

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 150 - 280 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13 (UPS and surge)
Output Voltage	AC 230 V 50/60 Hz
Power Capacity	700 Watt / 1400 VA
Dataline Surge Protection	Phone line - RJ-11
Output Waveform	Stepped approximation to a sinewave
Surge Suppression	Yes
Surge Energy Rating	273 Joules

Circuit Protection	Circuit breaker
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	2 min at full load 11 min at half load
Recharge Time	8 hours
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	USB
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B
Miscellaneous	
Cables Included	Power cable 1.22 m
Features	Audible alarm, audible alarm, Automatic Voltage Regulation (AVR), LED indicators, automatic self-test
Compliant Standards	C-Tick, IEC 62040-1-1, RoHS, A-Tick, REACH
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA
Dimensions & Weight	
Width	13 cm
Depth	33.6 cm
Height	21.5 cm
Weight	12 kg
Dimensions & Weight (Shipping)	
Shipping Width	24.5 cm
Shipping Depth	44 cm
Shipping Height	29.5 cm
Shipping Weight	12.94 kg