

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	PTEL2

APC ProtectNet - Surge protector - beige

Data line surges make up an overwhelming majority of all surge induced damages where the equipment was thought to be already protected but had a "back door" such as a modem line unprotected. Network interface cards, in particular, can be destroyed by relatively mild spikes. According to Ethernet standards (IEEE 802.3), non-AC network electrical hazards include: direct contact between components and power or lightning circuits, static charge buildup on cables and component, high-energy transients coupled onto the local cabling system (those induced by other cables which are installed in the general proximity of network cables or lightning within a mile radius) and potential differences (even from building to building, between safety grounds to which components are connected.)

Specifikation

General

Device Type	Surge protector - external
Colour	Beige
Localisation	Belgium, Bahrain, Jordan, Kuwait, Lebanon, Oman, Saudi Arabia, Yemen, United Arab Emirates, Afghanistan, Albania, Argentina, Armenia, Aruba, Australia, Benin, Bulgaria, Cameroon, China, Colombia, Cooks Island, Czech Republic, Estonia, Fiji, Indonesia, Israel, Lithuania, Papua New Guinea, Senegal, South Africa, Vietnam, Ukraine, Venezuela, Zaire, Belize, Canada, Chile, Egypt, Hong Kong, Iceland, Iran, Mexico, Myanmar, New Zealand, Pakistan, Romania, Sri Lanka, Taiwan, Thailand, Virgin Islands, Malaysia, Singapore, Puerto Rico, Luxembourg, Hungary, Cyprus, Brunei, Iraq, India, Ghana, Kenya, Sierra Leone, Nigeria, Malawi, Zambia, Uganda, Tanzania, Bolivia, Uruguay, Peru, Paraguay, Ecuador, Honduras, Guatemala, Costa Rica, Salvador, Panama, Nicaragua, Dominican Republic, Jamaica, Botswana, Angola, Algeria, Chad, Burkina Faso, Ethiopia, Falkland Isles, Cote D'Ivoire, Congo, Gabon, Mali, Liechtenstein, Gibraltar, Gambia, Lesotho, Mauritania, Malta, Somalia, Rwanda, Niger, Mozambique, Morocco, Togo, Zimbabwe, Sudan, Bangladesh, Cambodia, Philippines, Nepal, Yugoslavia, Belarus, Bosnia, Croatia, Kazakhstan, Macedonia, Slovakia, Slovenia, Korea, Latvia, Azerbaijan, Guyana, Uzbekistan, Moldova, Herzegovina, Georgia, Bhutan, Barbados, Antigua and Barbuda, Cayman Islands, East Timor, Cuba, Anguilla, Andorra, Burundi, Central African Republic, Djibouti, Equatorial Guinea, Guinea, Liberia, Namibia, Turkmenistan, Western

Sahara, Netherlands Antilles, Austria, Brazil, Denmark, Finland, France, Germany, Italy, Netherlands, Norway, Poland, Portugal, Russia, Spain, Sweden, Switzerland, United Kingdom, United States, Greece, Turkey, Ireland

Power Device

Surge Suppression	Yes
Surge Response Time	1 ns
Compliant Standards	UL, CSA, UL 497A

Expansion / Connectivity

Interfaces	1 x modem - RJ-45
-------------------	-------------------

Manufacturer Warranty

Service & Support	Limited warranty - remote monitoring - 10 years
------------------------------	---

Environmental Parameters

Min Operating Temperature	-15 °C
Max Operating Temperature	45 °C
Min Storage Temperature	-15 °C
Max Storage Temperature	45 °C
Humidity Range Operating	0 - 95%
Humidity Range Storage	0 - 95%

Dimensions & Weight

Width	4.8 cm
Depth	2.8 cm
Height	10.3 cm
Weight	60 g