

Produktinformation



Information

| | |
|--------------------|--------------------|
| <i>Tillverkare</i> | Schneider Electric |
| <i>Artnr</i> | SC620I |

APC Smart-UPS SC 620VA - UPS - AC 230 V - 390 Watt - 620 VA - RS-232 - output connectors: 4 - grey

APC Smart-UPS SC is the perfect protection for the IT resources of your growing business. Manageable and cost effective, APC Smart-UPS SC is designed for use by small and medium companies looking to protect networking equipment, providing both power and data-line protection. Included PowerChute Business Edition management software allows you to configure safe system shutdowns and take advantage of advanced UPS management features like automated risk assessments and runtime capacity calculations. Communications are through your server's standard serial port. When you are ready to take your business to the next level you can use the same software environment found on Smart-UPS SC to seamlessly manage other Smart-UPS models, allowing you to grow your IT infrastructure without having to replace your software or retrain your administrators. Built on the same standards as the award winning Smart-UPS UPS, the Smart-UPS SC is the UPS to start your business with.

Specifikation

General

| | |
|-------------------------------|----------------|
| Device Type | UPS - external |
| Battery Enclosure Type | Internal |
| Colour | Grey |

Power Device

| | |
|---|---|
| UPS Technology | Line interactive |
| Input Voltage | AC 230 V |
| Input Voltage Range | AC 160 - 286 V |
| Input Voltage Range (Adjustable) | AC 151 - 302 V |
| Frequency Provided | 50/60 Hz |
| Frequency Required | 50/60 Hz |
| Input Connectors | 1 x power IEC 60320 C14 |
| Power Output Connectors Details | 3 x power IEC 60320 C13 (UPS and surge) 1 x power IEC 60320 C13 (surge) |
| Output Voltage | AC 230 V \pm 5% - 50/60 Hz |

| | |
|------------------------------------|--|
| Power Capacity | 390 Watt / 620 VA |
| Dataline Surge Protection | Network/phone line - RJ-45/RJ-11 |
| Output Waveform | Stepped approximation to a sinewave |
| Surge Suppression | Yes |
| Surge Energy Rating | 320 Joules |
| Battery | |
| Quantity | 1 |
| Technology | Lead Acid |
| Run Time (Up To) | 5.5 min at full load |
| Networking | |
| Remote Management Interface | RS-232 |
| Expansion / Connectivity | |
| Interfaces | 1 x RS-232 - 9 pin D-Sub (DB-9) |
| Miscellaneous | |
| Cables Included | Serial cable |
| Features | Audible alarm, audible alarm, LED indicators |
| Compliant Standards | FCC Class B certified, CSA, NOM, UL 1449, UL 1778, FCC Part 15 |
| Manufacturer Warranty | |
| Service & Support | Limited warranty - parts and labour - 2 years |
| Environmental Parameters | |
| Min Operating Temperature | 0 °C |
| Max Operating Temperature | 40 °C |
| Humidity Range Operating | 0 - 95% |
| Sound Emission | 45 dBA |
| Dimensions & Weight | |
| Width | 11.9 cm |
| Depth | 36.8 cm |
| Height | 16.8 cm |
| Weight | 12 kg |