

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMC1500IC

APC Smart-UPS C 1500VA LCD - UPS - AC 230 V - 900 Watt - 1500 VA - USB - output connectors: 8 - black - with APC SmartConnect

This UPS has been tested and approved to work safely with the connected service provider equipment and within the specified environment.

Specifikation

General

Device Type	UPS - external
Colour	Black
Bundled with	APC SmartConnect

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 180 - 287 V
Input Voltage Range (Adjustable)	AC 170 - 300 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	50/60 Hz \pm 3%
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13
Output Voltage	AC 230 V \pm 5% - 50/60 Hz
Power Capacity	900 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules

Circuit Protection	Circuit breaker
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	4 min at full load 11 min at half load
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	USB
Expansion / Connectivity	
Interfaces	1 x management - RJ-45 1 x USB - 4 pin USB Type A
Miscellaneous	
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic shut down reset, automatic self-test, hot-swappable batteries, Green Function, auto restart, temperature-compensated battery charging
Compliant Standards	CSA, C-Tick, GOST, UL 1778, VDE
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA
Dimensions & Weight	
Width	17.1 cm
Depth	43.9 cm
Height	21.9 cm
Weight	24.09 kg
Dimensions & Weight (Shipping)	
Shipping Width	32.8 cm
Shipping Depth	59.5 cm
Shipping Height	37.6 cm
Shipping Weight	27.23 kg