

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMC1500I-2UC

APC Smart-UPS C SMC1500I-2UC - UPS (rack-mountable) - AC 220/230/240 V - 900 Watt - 1500 VA - RS-232, USB - output connectors: 4 - 2U - black - with APC SmartConnect

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Specifikation

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect

Power Device

UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 180 - 287 V
Input Voltage Range (Adjustable)	AC 170 - 300 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	50/60 Hz \pm 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13 2 x IEC jumper
Output Voltage	AC 230 V \pm 5% - 50/60 Hz
Power Capacity	900 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes

Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	10.1 min at full load 25 min at half load 173 min at 50 Watts 107 min at 100 Watts 59 min at 200 Watts 39.2 min at 300 Watts 28.6 min at 400 Watts 22.1 min at 500 Watts 17.6 min at 600 Watts 14.4 min at 700 Watts 12 min at 800 Watts 10.1 min at 900 Watts
Recharge Time	3 hours
Features	Maintenance free
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x serial - RJ-45
Miscellaneous	
Cables Included	Serial cable - external USB cable - external
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic shut down reset, automatic self-test, hot-swappable batteries
Compliant Standards	CSA, C-Tick, GOST, UL 1778, VDE
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	47.7 cm
Height	8.6 cm
Weight	28.64 kg
Dimensions & Weight (Shipping)	
Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.91 kg