

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMT1500RMI2UC

APC Smart-UPS 1500VA LCD RM - UPS (rack-mountable) - AC 220/230/240 V - 1 kW - 1500 VA - RS-232, USB - output connectors: 4 - 2U - black - with APC SmartConnect - for P/N: AR106V, AR106VI, AR112SH6, AR3006, AR3006SP, AR3103, AR3103SP, AR3106, AR3106SP

Intuitive LCD interface provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys. Predictive replace battery date dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.

Specifikation

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect

Power Device

UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	57 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V 57 - 63 Hz

Power Capacity	1 kW / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
Battery	
Technology	Lead Acid
Run Time (Up To)	7.2 min at full load
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - RJ-45
Expansion Slots	1 SmartSlot
Miscellaneous	
Cables Included	Serial cable USB cable
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
Software / System Requirements	
Software Included	Drivers & Utilities
Environmental Standards	
ENERGY STAR	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA
Dimensions & Weight	

Width	43.2 cm
Depth	47.7 cm
Height	8.6 cm
Weight	26.1 kg

Dimensions & Weight (Shipping)

Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.91 kg

Compatibility Information

Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR106V, AR106VI, AR112SH6, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3003SP, AR3006, AR3006SP, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X432, AR7007, AR7050, AR7057, NBWL0356A
---------------------	--