

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMT1500RMI2UNC

APC Smart-UPS 1500VA LCD RM - UPS (rack-mountable) - AC 230 V - 1 kW - 1500 VA - Ethernet, RS-232, USB - output connectors: 4 - 2U - black - with APC UPS Network Management Card - for P/N: AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, NBWL0356A

Intuitive LCD interface provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys. Predictive replace battery date dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.

Specifikation

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC UPS Network Management Card

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Required	50 Hz \pm 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	Power IEC 60320 C13
Output Voltage	AC 230 V \pm 5%
Power Capacity	1 kW / 1500 VA

Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker

Battery

Technology	Lead Acid
Run Time (Up To)	7 min at full load 26 min at half load
Recharge Time	3 hours
Transfer Time	2 ms
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	Ethernet, RS-232, USB
------------------------------------	-----------------------

Expansion / Connectivity

Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB) - 4 pin USB Type B Management (USB) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot

Miscellaneous

Included Accessories	Rack mounting rails, temperature probe
Cables Included	Serial cable - external USB cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
------------------------------	---

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA

Dimensions & Weight

Width	43.2 cm
Depth	45.7 cm
Height	8.9 cm
Weight	28.58 kg

Dimensions & Weight (Shipping)

Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.84 kg

Compatibility Information

Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF202BLK, ACF400, ACF402, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR201, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, NBP0180, NBRK0201, NBRK0320, NBRK0320E, NBRK0551, NBWL0355, NBWL0356A
---------------------	--