

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMT750RMI2UC

APC Smart-UPS 750VA LCD RM - UPS (rack-mountable) - AC 230 V - 500 Watt - 750 VA - Ethernet, RS-232, USB - output connectors: 4 - 2U - black - for P/N: AR3103SP, AR3106SP, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, NBWL0356A

APC Smart-UPS protects your data by supplying reliable, network-grade power in either traditional Tower or Rack-optimized form factors for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical file servers (Intel or UNIX based), minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs. Rack Mount versions are the choice for rack optimized servers, server appliances, blade servers, other blade devices and rack-mounted network switches and hubs.

Specifikation

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 150 - 300 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz \pm 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13
Output Voltage	AC 230 V 50/60 Hz

Power Capacity 500 Watt / 750 VA

Output Waveform Sinewave

Surge Suppression Yes

Battery

Technology Lead Acid

Run Time (Up To) 6 min at full load 5 min at 500 Watts 24 min at 200 Watts

Recharge Time 3 hours

Features Maintenance free, sealed, leak-proof

Networking

Remote Management Interface Ethernet, RS-232, USB

Expansion / Connectivity

Interfaces 1 x management (RS-232) - RJ-45 1 x management (USB) - 4 pin USB
Type B Management (Ethernet) - RJ-45

Expansion Slots 1 (total) / 1 (free) x SmartSlot

Miscellaneous

Features Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, energy metre

Compliant Standards VDE, EN 62040-2, RCM, EN 62040-1

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Humidity Range Operating 0 - 95%

Sound Emission 42 dBA

Dimensions & Weight

Width 43.2 cm

Depth 40.9 cm

Height 8.6 cm

Weight 21.23 kg

Compatibility Information

Designed For P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF002, ACF102BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106SP, AR3107, AR3107G, AR3107SP,

AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140,
AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2,
AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155,
AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609,
AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP,
AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305,
AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609,
AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347,
AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610,
AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP,
AR3357X609, AR3357X610, AR3357X617, AR4018, AR4018A,
AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432,
AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432,
AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A,
AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432,
AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432,
AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A,
AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432,
AR4038X432, AR7050, NBWL0356A