

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMT750RMI2UNC

APC Smart-UPS 750VA LCD RM - UPS (rack-mountable) - AC 230 V - 500 Watt - 750 VA - Ethernet, RS-232, USB - output connectors: 4 - 2U - black - with APC UPS Network Management Card - for P/N: AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, NBWL0356A

APC Smart-UPS protects your data by supplying reliable, network-grade power in either traditional Tower or Rack-optimized form factors for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical file servers (Intel or UNIX based), minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs. Rack Mount versions are the choice for rack optimized servers, server appliances, blade servers, other blade devices and rack-mounted network switches and hubs.

Specifikation

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC UPS Network Management Card

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Required	50 Hz \pm 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	Power IEC 60320 C13

Output Voltage	AC 230 V ± 5%
Power Capacity	500 Watt / 750 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker

Battery

Technology	Lead Acid
Run Time (Up To)	5.5 min at full load 16 min at half load
Recharge Time	3 hours
Transfer Time	2 ms
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	Ethernet, RS-232, USB
------------------------------------	-----------------------

Expansion / Connectivity

Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB) - 4 pin USB Type B Management (USB) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot

Miscellaneous

Included Accessories	Rack mounting rails, temperature probe
Cables Included	Serial cable - external USB cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
------------------------------	---

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	42 dBA

Dimensions & Weight

Width	43.2 cm
Depth	40.6 cm

Height	8.9 cm
Weight	17.24 kg

Dimensions & Weight (Shipping)

Shipping Width	54.6 cm
Shipping Depth	58.4 cm
Shipping Height	24.1 cm
Shipping Weight	21.18 kg

Compatibility Information

Designed For	<p>P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF202BLK, ACF400, ACF402, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR201, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, NBP0180, NBRK0201, NBRK0320, NBRK0320E, NBRK0551, NBWL0355, NBWL0356A, SYA8K8RMI</p>
---------------------	--