


## Produktinformation



## Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMTL750RMI2UC

**APC Smart-UPS Li-Ion 750VA Short Depth with SmartConnect - UPS (rack-mountable / external) - AC 230 V - 600 Watt - 750 VA - RS-232, USB - output connectors: 6 - 2U - black - for P/N: AR106V, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432**

## Specifikation

### General

<b>Device Type</b>	UPS - rack-mountable / external
<b>Height (Rack Units)</b>	2U
<b>Colour</b>	Black

### Power Device

<b>UPS Technology</b>	Line interactive
<b>Input Voltage</b>	AC 230 V
<b>Input Voltage Range</b>	AC 160 - 286 V
<b>Input Voltage Range (Adjustable)</b>	AC 151 - 302 V
<b>Frequency Provided</b>	50/60 Hz $\pm$ 3Hz
<b>Frequency Required</b>	50/60 Hz $\pm$ 3Hz
<b>Input Connectors</b>	Power IEC 60320 C14
<b>Power Output Connectors Details</b>	6 x power IEC 60320 C13
<b>Output Voltage</b>	AC 230 V $\pm$ 5% - 50/60 Hz
<b>Power Capacity</b>	600 Watt / 750 VA
<b>Output Waveform</b>	Sinewave
<b>Surge Suppression</b>	Yes
<b>Surge Energy Rating</b>	645 Joules

Battery	
<b>Technology</b>	Lithium ion
<b>Recharge Time</b>	3 hours
Networking	
<b>Remote Management Interface</b>	RS-232, USB
Expansion / Connectivity	
<b>Interfaces</b>	1 x management (RS-232) - RJ-45 1 x management (USB)
<b>Expansion Slots</b>	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
<b>Features</b>	Audible alarm, LCD display
<b>Compliant Standards</b>	NOM, UL 1449, UL 1778, CSA C22.2 No. 107.1, RoHS, FCC Part 15 A, REACH, IP20
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 5 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	0 - 95% (non-condensing)
<b>Sound Emission</b>	45 dB
Dimensions & Weight	
<b>Width</b>	43.8 cm
<b>Depth</b>	31.8 cm
<b>Height</b>	8.6 cm
<b>Weight</b>	17.69 kg
Dimensions & Weight (Shipping)	
<b>Shipping Width</b>	58.4 cm
<b>Shipping Depth</b>	47.2 cm
<b>Shipping Height</b>	22.9 cm
<b>Shipping Weight</b>	18.6 kg
Compatibility Information	
<b>Designed For</b>	P/N: ACCS1001, ACDC1015, ACDC1019, AP5607, AP9290, AR106V, AR204A, AR3150SP2, AR3300W, AR3350W, AR3357X610, AR3357X617, AR4018A, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432