

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SMV750CAI

APC Easy UPS SMV SMV750CAI - UPS - AC 220/230/240 V - 525 Watt - 750 VA 7 Ah - RS-232, USB - output connectors: 6

Specifikation

General

Device Type UPS - external

Power Device

UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 295 V
Frequency Provided	50/60 Hz \pm 1Hz
Frequency Required	45 - 65 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13
Output Voltage	AC 230 V 50/60 Hz
Power Capacity	525 Watt / 750 VA
Output Waveform	Sinewave
Circuit Protection	Fuse

Battery

Quantity	2
Technology	Lead Acid
Voltage Provided	12 V
Capacity	7 Ah
Recharge Time	4 hours
Transfer Time	2 ms
Features	Maintenance free, sealed, leak-proof

Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - 9 pin D-Sub (DB-9)
Miscellaneous	
Cables Included	2 x power cable - external USB cable - external
Features	LCD display
Compliant Standards	IP20
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Sound Emission	45 dBA
Dimensions & Weight	
Width	16 cm
Depth	41 cm
Height	22 cm
Weight	13.6 kg
Dimensions & Weight (Shipping)	
Shipping Width	27.2 cm
Shipping Depth	50.8 cm
Shipping Height	33.9 cm
Shipping Weight	16.6 kg