

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SRT1500RMXLI

APC Smart-UPS SRT 1500VA RM - UPS (rack-mountable / external) - AC 220/230/240 V - 1.5 kW - 1500 VA - RS-232, USB - output connectors: 6 - PFC - 2U - black

Battery failure notification provides early-warning fault analysis on batteries enabling timely preventive maintenance. ECO Mode by-passes unused electrical components in good power conditions to achieve high operating efficiency without sacrificing protection. Text and mimic diagrams display modes of operation, system parameters and alarms.

Specifikation

General

Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Height (Rack Units)	2U
Colour	Black

Power Device

UPS Technology	On-line
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 50 - 150 / 80 - 150 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	40 - 70 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V \pm 2% - 50/60 Hz
Power Capacity	1.5 kW / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	432 Joules
Circuit Protection	Circuit breaker

Efficiency	92% at 100% Load
Battery	
Technology	Lead Acid
Run Time (Up To)	4 min at 1500 Watts 14.6 min at 750 Watts
Recharge Time	3 hours
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (RS-232) - RJ-45 1 x EPO (emergency power off) 1 x management (USB)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	Power cable 1.83 m Serial cable - external USB cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, internal bypass, LED indicators, cold-start function, firmware upgradable, automatic self-test, hot-swappable batteries, Eco-Mode, reset breaker
Compliant Standards	RoHS, IP20, EAC
Software / System Requirements	
Software Included	Drivers & Utilities
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Sound Emission	50 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	50.5 cm
Height	8.5 cm
Weight	22 kg
Dimensions & Weight (Shipping)	
Shipping Width	59.4 cm
Shipping Depth	74.9 cm
Shipping Height	24.6 cm

Shipping Weight

26.9 kg