

## Produktinformation



### Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SRV1KRILRK

## APC Easy UPS SRV SRV1KRILRK - UPS (rack-mountable) - AC 220/230/240 V - 800 Watt - 1000 VA - RS-232, USB - output connectors: 4 - PFC - with Rail Kit

## Specifikation

### General

<b>Device Type</b>	UPS - Power Factor Correction (PFC) - rack-mountable
<b>Bundled with</b>	Rail Kit

### Power Device

<b>UPS Technology</b>	On-line
<b>Input Voltage</b>	AC 220/230/240 V
<b>Input Voltage Range</b>	AC 160 - 280 V
<b>Frequency Provided</b>	50/60 Hz $\pm$ 3Hz
<b>Frequency Required</b>	40 - 70 Hz
<b>Input Connectors</b>	1 x power IEC 60320 C14
<b>Power Output Connectors Details</b>	4 x power IEC 60320 C13
<b>Output Voltage</b>	AC 220/230/240 V 50/60 Hz
<b>Power Capacity</b>	800 Watt / 1000 VA
<b>Output Waveform</b>	Sinewave
<b>Surge Suppression</b>	Yes
<b>Surge Energy Rating</b>	600 Joules
<b>Efficiency</b>	88%

### Battery

<b>Technology</b>	Lead Acid
<b>Run Time (Up To)</b>	52 min at half load 23.7 min at full load
<b>Recharge Time</b>	4 hours

<b>Features</b>	Maintenance free, sealed, leak-proof
Networking	
<b>Remote Management Interface</b>	RS-232, USB
Expansion / Connectivity	
<b>Interfaces</b>	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - 9 pin D-Sub (DB-9)
<b>Expansion Slots</b>	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
<b>Cables Included</b>	USB cable - external
<b>Features</b>	Audible alarm, LCD display, internal bypass, LED indicators, automatic self-test, Eco-Mode, Intelligent Battery Management
<b>Compliant Standards</b>	IEC 62040-1-1, RoHS, REACH, IP20, IEC 62040-1-2
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 2 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	0 - 95% (non-condensing)
Dimensions & Weight	
<b>Width</b>	43.8 cm
<b>Depth</b>	41.2 cm
<b>Height</b>	17.2 cm
<b>Weight</b>	27 kg
Dimensions & Weight (Shipping)	
<b>Shipping Width</b>	50 cm
<b>Shipping Depth</b>	60 cm
<b>Shipping Height</b>	48 cm
<b>Shipping Weight</b>	33.5 kg