

Produktinformation



Information

<i>Tillverkare</i>	Schneider Electric
<i>Artnr</i>	SRV2KRILRK

APC Easy UPS SRV SRV2KRILRK - UPS (rack-mountable) - AC 220/230/240 V - 1600 Watt - 2000 VA - RS-232, USB - output connectors: 4 - PFC - with Rail Kit

Specifikation

General

Device Type	UPS - Power Factor Correction (PFC) - rack-mountable
Bundled with	Rail Kit

Power Device

UPS Technology	On-line
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 280 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	40 - 70 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V 50/60 Hz
Power Capacity	1600 Watt / 2000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	600 Joules
Efficiency	88%

Battery

Technology	Lead Acid
Run Time (Up To)	49.6 min at half load 22.3 min at full load
Recharge Time	4 hours

Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - 9 pin D-Sub (DB-9)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	USB cable - external
Features	Audible alarm, LCD display, internal bypass, LED indicators, automatic self-test, Eco-Mode, Intelligent Battery Management
Compliant Standards	IEC 62040-1-1, RoHS, REACH, IP20, IEC 62040-1-2
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Dimensions & Weight	
Width	43.7 cm
Depth	63.2 cm
Height	17.2 cm
Weight	51.7 kg
Dimensions & Weight (Shipping)	
Shipping Width	60 cm
Shipping Depth	80 cm
Shipping Height	48 cm
Shipping Weight	66.5 kg