

Produktinformation



Information



Tillverkare Synology
Artnr RS3617RPXS

Synology RackStation RS3617RPxs - NAS server - 12 bays - rack-mountable - SATA 6Gb/s - RAID 0, 1, 5, 6, 10, JBOD - RAM 8 GB - Gigabit Ethernet - iSCSI - 2U

Designed for businesses seeking large data storage capacity, RS3617RPxs is a high-performance, 12-bay rackmount NAS equipped with redundant power supplies, ensuring business continuity. Organizations can integrate seamlessly with virtualization solutions.

Specifikation

General

Device Type	NAS server
Host Connectivity	Gigabit Ethernet
Enclosure Type	Rack-mountable - 2U
Total Storage Capacity	0 GB
Max Supported Capacity	144 TB
Installed Devices / Modules Qty	0 (installed) / 12 (max)
Width	69.2 cm
Depth	43.05 cm
Height	8.8 cm
Weight	14.5 kg

Processor / Memory

Processors Installed	1 x Intel Xeon D-1521 2.4 GHz
Number of Cores	Quad-Core
Max Supported Qty	1
RAM	8 GB (installed) / 64 GB (supported) - DDR4

Storage Controller

Type	RAID
-------------	------

Interface Type	SATA 6Gb/s
RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, JBOD
Networking	
Data Link Protocol	10Mb LAN, 100Mb LAN, GigE
Network / Transport Protocol	L2TP, iSCSI
Remote Management Protocol	SNMP, Telnet, HTTPS
Network Services Compatibility	Microsoft Active Directory (AD), Network File System (NFS), Server Message Block (SMB), Apple File Protocol (AFP), Web-based Distributed Authoring and Versioning (WebDAV), Calendaring Extensions to WebDAV (CalDAV)
Features	Firewall protection, LDAP support, wake on LAN (WOL), antivirus analysis, Access Control List (ACL) support, iTunes server, UPnP Media Server, surveillance station, DLNA Media Server, cloud backup, VPN Server
Encryption Algorithm	AES, SSL, TLS
Compliant Standards	DLNA CERTIFIED
Security DVR	
IP Cameras Supported	75
Expansion / Connectivity	
Expansion Bays	12 (total) / 12 (free) x hot-swap - 2.5" / 3.5"
Expansion Slots	2 (total) / 2 (free) x PCI Express 3.0 x8
Interfaces	4 x Ethernet 1000Base-T - RJ-45 2 x USB 2.0 - Type A 2 x USB 3.0 - Type A 1 x serial - DB-9 2 x InfiniBand
Miscellaneous	
Compliant Standards	FCC Class A certified, RoHS, BSMI Class A
Power	
Power Device	Internal power supply
Installed Qty	2
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	500 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 5 years
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	5 - 95%