

Produktinformation



Information



Tillverkare Synology

Artnr RS3618XS

Synology RackStation RS3618XS - NAS server
- 12 bays - rack-mountable - SATA 6Gb/s -
RAID 0, 1, 5, 6, 10, JBOD, RAID F1 - RAM 8 GB
- Gigabit Ethernet - iSCSI - 2U

Specifikation

General

| | |
|--|---------------------------|
| Device Type | NAS server |
| Host Connectivity | Gigabit Ethernet |
| Enclosure Type | Rack-mountable - 2U |
| Total Storage Capacity | 0 GB |
| Installed Devices / Modules Qty | 12 (installed) / 12 (max) |
| Width | 43.05 cm |
| Depth | 69.2 cm |
| Height | 8.8 cm |

Processor / Memory

| | |
|-----------------------------|---|
| Processors Installed | 1 x Intel Xeon D-1521 2.4 GHz |
| Number of Cores | Quad-Core |
| Max Supported Qty | 1 |
| Max Turbo Speed | 2.7 GHz |
| RAM | 8 GB (installed) / 64 GB (supported) - DDR4 |

Storage Controller

| | |
|-----------------------|--|
| Type | RAID |
| Interface Type | SATA 6Gb/s |
| RAID Level | RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, JBOD, RAID F1 |

Networking

| | |
|---------------------------|---------------------------|
| Data Link Protocol | 10Mb LAN, 100Mb LAN, GigE |
|---------------------------|---------------------------|

| | |
|---------------------------------------|---|
| Network / Transport Protocol | L2TP, iSCSI |
| Remote Management Protocol | SNMP, Telnet, HTTPS |
| Network Services Compatibility | Microsoft Active Directory (AD), Network File System (NFS), Server Message Block (SMB), Apple File Protocol (AFP), Web-based Distributed Authoring and Versioning (WebDAV), Calendaring Extensions to WebDAV (CalDAV) |
| Features | Firewall protection, LDAP support, wake on LAN (WOL), antivirus analysis, Access Control List (ACL) support, iTunes server, UPnP Media Server, surveillance station, DLNA Media Server, cloud backup, VPN Server |
| Encryption Algorithm | AES, SSL, TLS |
| Compliant Standards | DLNA CERTIFIED |
| Expansion / Connectivity | |
| Expansion Bays | 12 (total) / 12 (free) x hot-swap - 2.5" / 3.5" |
| Expansion Slots | 2 (total) / 2 (free) x PCI Express x8 |
| Interfaces | 4 x Ethernet 1000Base-T - RJ-45 2 x USB 3.0 - Type A |
| Miscellaneous | |
| Features | Wake on LAN, built-in 4 cooling fans |
| Compliant Standards | FCC Class A certified, RoHS, BSMI Class A |
| Power | |
| Power Device | Internal power supply |
| Installed Qty | 1 |
| Max Supported Qty | 1 |
| Voltage Required | AC 120/230 V (50/60 Hz) |
| Power Provided | 500 Watt |
| Environmental Parameters | |
| Min Operating Temperature | 5 °C |
| Max Operating Temperature | 35 °C |
| Humidity Range Operating | 5 - 95% |