

Produktinformation



Information

| | |
|--------------------|--------------------|
| <i>Tillverkare</i> | ads-tec |
| <i>Artnr</i> | DVG-ITC8113 107-BZ |

ads-tec TabX ITC8000 series ITC8113 - 13.3" - Celeron 2980U - 8 GB RAM - 120 GB SSD

The industrial tablet computers from ADS-TEC have undergone consistent further development for professional mobile use. High performance, brilliant high-resolution display and optimized for applications in service environments - the TabX ITC8113 scores high marks both for indoor and outdoor use.

Specifikation

General

Product Type Tablet - no keyboard

Operating System Windows 10

Processor / Chipset

CPU Intel Celeron 2980U / 1.6 GHz

Number of Cores Dual-Core

Cache 2 MB

64-bit Computing Yes

Features Integrated memory controller

Memory

RAM 8 GB (provided memory is soldered)

Technology DDR3 SDRAM

Storage

Main Storage 120 GB SSD

Display

Type 13.3"

LCD Backlight Technology LED backlight

Touchscreen Yes (10-point multi-touch)

Resolution 1920 x 1080 (Full HD)

| | |
|--|---|
| Widescreen | Yes |
| Features | Anti-reflective |
| Audio & Video | |
| Graphics Processor | Intel HD Graphics |
| Camera | Yes |
| Resolution | 5 Megapixel |
| Camera Features | Autofocus |
| Sound | Stereo speakers, microphone |
| Communications | |
| Wireless | 802.11a/b/g/n, Bluetooth 4.0 |
| Bluetooth Class | Class 2 |
| Network Interface | Gigabit Ethernet |
| Battery | |
| Technology | Lithium Ion |
| Installed Qty | 2 |
| Capacity | 40 Wh |
| Run Time With Included Additional Battery | Up to 7.83 hours |
| AC Adapter | |
| Input | AC 100 - 240 V (50/60 Hz) |
| Output | 70 Watt, 20 V |
| Connections & Expansion | |
| Interfaces | 3 x USB 3.0 DisplayPort Headphone/microphone combo jack LAN Dock |
| Miscellaneous | |
| Case Material | Glass-fibre |
| Dockable | Yes |
| Features | Shock-resistant, vibration |
| Included Accessories | Power adapter |
| Compliant Standards | IP65, IP53, RoHS 2011/65/EU, EMC 2014/30/EU, LVD 2014/35/EU, RED 2014/53/EU |
| Dimensions & Weight | |
| Dimensions (WxDxH) | 35.6 cm x 26.2 cm x 4.2 cm |
| Weight | 1.8 kg |
| Environmental Parameters | |
| Min Operating Temperature | 0 °C |
| Max Operating Temperature | 40 °C |
| Humidity Range Operating | 10 - 85% (non-condensing) |