

## Produktinformation



### Information

<i>Tillverkare</i>	ads-tec
<i>Artnr</i>	DVG-ITC8113 108-BZ

## ads-tec TabX ITC8000 series ITC8113 - 13.3" - Celeron 2980U - 8 GB RAM - 120 GB SSD

The industrial tablet computers from ADS-TEC have undergone consistent further development for professional mobile use. High performance, brilliant high-resolution display and optimized for applications in service environments - the TabX ITC8113 scores high marks both for indoor and outdoor use.

## Specifikation

### General

**Product Type** Tablet - no keyboard

**Operating System** Windows 10

### Processor / Chipset

**CPU** Intel Celeron 2980U / 1.6 GHz

**Number of Cores** Dual-Core

**Cache** 2 MB

**64-bit Computing** Yes

**Features** Integrated memory controller

### Memory

**RAM** 8 GB (provided memory is soldered)

**Technology** DDR3 SDRAM

### Storage

**Main Storage** 120 GB SSD

### Display

**Type** 13.3"

**LCD Backlight Technology** LED backlight

**Touchscreen** Yes (10-point multi-touch)

**Resolution** 1920 x 1080 (Full HD)

<b>Widescreen</b>	Yes
<b>Features</b>	Anti-reflective
Audio & Video	
<b>Graphics Processor</b>	Intel HD Graphics
<b>Camera</b>	Yes
<b>Resolution</b>	5 Megapixel
<b>Camera Features</b>	Autofocus
<b>Sound</b>	Stereo speakers, microphone
Communications	
<b>Wireless</b>	802.11a/b/g/n, Bluetooth 4.0
<b>Bluetooth Class</b>	Class 2
<b>Network Interface</b>	Gigabit Ethernet
Wireless Broadband (WWAN)	
<b>Generation</b>	4G
<b>Technology</b>	LTE
Battery	
<b>Technology</b>	Lithium Ion
<b>Installed Qty</b>	2
<b>Capacity</b>	40 Wh
<b>Run Time With Included Additional Battery</b>	Up to 7.83 hours
AC Adapter	
<b>Input</b>	AC 100 - 240 V (50/60 Hz)
<b>Output</b>	70 Watt, 20 V
Connections & Expansion	
<b>Interfaces</b>	3 x USB 3.0 DisplayPort Headphone/microphone combo jack LAN Dock
Miscellaneous	
<b>Case Material</b>	Glass-fibre
<b>Dockable</b>	Yes
<b>Features</b>	Shock-resistant, vibration
<b>Included Accessories</b>	Power adapter
<b>Compliant Standards</b>	IP65, IP53, RoHS 2011/65/EU, EMC 2014/30/EU, LVD 2014/35/EU, RED 2014/53/EU
Dimensions & Weight	
<b>Dimensions (WxDxH)</b>	35.6 cm x 26.2 cm x 4.2 cm
<b>Weight</b>	1.8 kg
Environmental Parameters	

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 85% (non-condensing)